

KVM-6500-17/19/20 LCD KVM Console



The single-rail modular LCD KVM features an integrated 17"/19"/20" TFT LCD color display, one set of industrial keyboard and touchpad. With the modular design, user only needs to take off few screws and any module can be easily detached/ re-attached again. Module replacement can be implemented with ease. Besides, a 8/16-port KVM module in 1U format design allows user to add to be a 8/16 port LCD KVM in use.

FEATURES

- * Integrated KVM module with 17"/19"/20" LCD monitor 、 keyboard/ touch pad module
- * A 8 or 16 port KVM switch within 1U chassis can be added
- * Support combo KVM module to connect servers via USB & PS/2 connection
Support single rail for independent access to panel and keyboard tray
- * Modular design for easy replacement and maintenance
- * Comply with EIA RS-310C 19" rack mount standard
- * Support high resolution up to 1280 x 1024 @ 75Hz
- * Heavy-duty electroplate steel

SPECIFICATIONS

Model number	KVM-6500-17	KVM-6500-19	KVM-6500-20
LCD Size	17"	19"	20.1"
Display Color	16.7M	16.2M	16.2M
Contrast	1000:1	1000:1	650:1
Luminance	300cd/m ²	300cd/m ²	300cd/m ²
Viewing Angle	H 80/80(160°) 、V80/80(160°)	H 85/85(170°) 、V80/80(160°)	H 70/60(130°) 、V75/75(150°)
Pixel	0.264*0.264	0.294*0.294	0.2916*0.2916
Console Port	HDDB 15pin (shared with VGA,PS2 keyboard and Mouse)		
Keyboard Emulation	PS/2		
Mouse Emulation	PS/2		
VGA Resolution	Max. 1280x1024 (Limited by TFT LCD monitor)		
Housing	Metal		
Power in	DC 12V 4A (with one AC to DC power Adapter)		
Operation Temperature	0~50°C		
Storage Temperature	-20 ~ 60°C		
Humidity	10~90%, Non-Condensing		
Size	482*610*44mm (WLH) , 19" Rack Mount / 1U		
Safety	CE, FCC approved.		