

SC-485SN RS-232 to RS-422/ 485 Converter



RS-232 to RS-422/ 485 Converter, None-power

FEATURES

- RS232 to RS422/ 485 converter
 - RS422/485 line Surge protected
 - Non power operation.
 - Auto switching baud rate, speed up to 115.2kbps over a distance 1,250M.
 - Select RS-422 or RS-485 by DIP SWITCH
- RS-422 / 485 Connector : Terminal
 RS-422 Signal : TxD+, TxD-, RxD+ , RxD-
 RS-485 Signal : Data+, Data-
 Mode : 4-wire RS-422, 2-wire RS-485
 Surge Protect : 15 KV ESD
 Power Protect : YES



SPECIFICATIONS

SPECIFICATION	SC-485SN
INPUT	RS-232, 1 x DB-9/M
OUTPUT	RS-422, 4-pin terminal block RS-485, 2-pin terminal block
Baud Rate	110~115,200bps
Environment	Operating Temp : 0~60°C Storage Temp : -20 to 85°C Humidity : 5~95 % RH
Dimension	55*40*25 mm (WDH)
Transmission Distance	1,250 meters
LED	TX, RX
Power Consumption	DC 5V(Non-powered), 20mA (max.)
安規認證	CE, FCC