

URI-128i USB to RS-422/485 工規轉換器



USB to 1- port RS-422/485 high speed up to 921K ,
 3KV Optical Isolation ,
 600W Surge Adapter ,
 With DIM Rail and Wall Mount kit

產品特性

- High Speed Baud Rate up to 921.6Kbps ◦
- USB 1.0/1.1 compliant, USB 2.0 Full Speed compatible ◦
- 12Mbps USB Data Rate ◦
- Built-in Terminator 120 ohm for DIP Switch Setting ◦
- 32 Device Connectivity for RS-485 Max. ◦
- Transmit and Receive LED supports ◦
- 3KV Optical Isolation Protection ◦
- 600W Surge Protection ◦
- Built-in 15KV ESD protection for all Serial Port and RS-422/485 Signals Protection ◦
- Supports Industrial Specification
- TX buffer 128 bytes and RX buffer 256 bytes
- Supports Microsoft Windows, Linux, and MAC drivers ◦

產品規格

SPECIFICATION	URI-128i
Hardware	Communication controller: FTDI – USB to Serial Controller Device Connector: Terminal Block 5-pin 5.08mm Host Connector: Mini USB B Type

Serial Interface	Number of ports: 1 port Serial Standard: RS-422/485 IRQ and I/O Address: Assigned by BIOS
Serial Line Protection	ESD Protection: 15KV ESD Protection for all signals Optical Isolation Protect: 3KV Opto Isolation\ Surge Protection : 600W Surge Protect for RS-422/485
Performance	Baud rate: up to 921.6 Kbps FIFOs: TX Buffer 128 bytes, RX Buffer 256 bytes
Serial Communication Parameters	Data Bits: 7, 8 Stop Bits: 1, 2 Parity: None, Even, Odd, Space, Mark
Serial Signals	RS-422: Tx+, Tx-, Rx+, Rx-, GND 4 Wire RS-485(RS-422 Multi-Drop): Tx+, Tx-, Rx+, Rx-, GND RS-485(2 Wire RS-485) : Data+, Data-, GND
Driver Support	Windows: XP, 2003, Vista, 2008, Win 7 Linux: 2.4 and 2.6 MAC: 8/9/X
Environmental Limits	Operating Temperature: -30 ~ 75°C Storage Temperature: -40 ~ 85°C Ambient Relative Humidity: 5 ~ 95% Non-Condensing
Standards and Certifications	CE and FCC supports
Package Content	USB to 1 port RS-422/485 3KV Isolation 600W Surge Adapter x 1 DIN Rail Kit x 1 USB Mini B Type to USB A type Cable 100cm x 1 Quick Instill Guide x 1 Driver CD x 1