

KVM6500S-19 LCD KVM SWITCH




單埠 KVM 電腦操控台(含 19"LCD 及鍵盤滑鼠觸控板) 安裝在 19 吋的短距型機櫃內，占 1U 高度。

此系列入門機種為單埠基本型，有 LCD 17 吋/19 吋供選擇，另可加裝 8 埠/16 埠 KVM 或 IP KVM 模組。全機模組化組成，可輕易拆卸更換 LCD 面板、鍵盤滑鼠 及 KVM Switch。

產品功能

- 支援 1U 機架型抽拉式含可收納式 19 吋 LCD 顯示器、鍵盤及 Touch Pad。
- 本體不含 KVM 全長 433mm，若加裝 8/16 埠 KVM 全長 540mm。
- LCD 顯示器、鍵盤滑鼠可模組化組裝方便拆卸更換。
- LCD 顯示器可模組化更換 17, 19 吋等二種尺寸的螢幕。
- 使用 105 鍵薄膜式鍵盤及含左右鍵的滑鼠觸控板(Touch Pad)。
- 適用機架滑軌長度範圍為 440~800mm (機器本體全長 434mm)。
- 機體符合 EIA 310C 及 IEC-3 規範。
- 須可提供三種輸入電源模式購買選擇: AC 100-240V, DC24V, DC-48V 輸入。
- 台灣製造 -品質保障。



產品規格

規格	KVM6500S-19
Resolution (解晰度)	1280x1024@60Hz
Display Color (色彩)	16.7 M (百萬色)
Contrast (對比)	1000:1
Luminance (亮度)	250cd/m ²
Viewing Angle (可視角)	水平 85/85(170°)、垂直 80/80(160°)
Pixel (點距)	0.294*0.294
Console Port	HDDB 15pin (shared with VGA,PS2 keyboard and Mouse)
PC selection	On Screen Display Manual, Hot-Keys
Keyboard Emulation	PS/2
Mouse Emulation	PS/2
VGA Resolution	Max 1280x1024 (Limited by TFT LCD monitor)
Housing	Metal
Power in	DC 12V 4A (with one AC to DC power Adapter)
Operation Temperature	0 ~50°C
Storage Temperature	-20 ~ 60°C
Humidity	10~80%, Non-Condensing
Size (W/O KVM)	482*433*44mm (WLH) , 19" Rack Mount / 1U
Weight	18 KGS